



DECLARATION OF PERFORMANCE

No. CPR 305/2011 - NOV 2024

BS EN 14179: GLASS IN BUILDING HEAT SOAKED THERMALLY TOUGHENED SODA LIME SILICATE SAFETY GLASS

THIS DECLARATION CONFIRMS THE COMPANY BELOW HAVE CONFORMED WITH EN 14179-2 ANNEX ZA
INTENDED USE: GLASS IN BUILDINGS AND CONSTRUCTION WORKS



SPECIALIST GLASS PRODUCTS LIMITED

**MILNSBRIDGE BUSINESS CENTRE, COLNE VALLEY ROAD,
MILNSBRIDGE, HUDDERSFIELD, WEST YORKSHIRE. HD3 4NY**

AVCP LEVEL 3

(a) SUBMITTING GLASS FOR INITIAL TYPE TESTING TO EN 14179, EN12600 & EN1288 AND SUCCESSFULLY MEETING ALL REQUIREMENTS.

Characteristics	5mm	6mm	8mm	10mm	12mm	15mm	19mm
Resistance to Fire	NPD						
Reaction to Fire	A1						
External Fire Performance	NPD						
Bullet Resistance	NPD						
Explosion Resistance	NPD						
Burglar Resistance	NPD						
Pendulum Body Impact Resist	1(c)1	1(c)1	1(c)1	1(c)1	1(c)1	1(c)1	1(c)1
Resistance Against Sudden Temperature Changes	200k	200k	NPD	NPD	NPD	NPD	NPD
Wind, snow permanent and imposed load resistance	4mm	6mm	NPD	NPD	NPD	NPD	NPD
Direct airborne sound insulation	29 (-2; -3) dB	31 (-2; -3) dB	NPD	NPD	NPD	NPD	NPD
Thermal Properties	5.8W/(m2K)	5.7W/(m2K)	NPD	NPD	NPD	NPD	NPD
Radiation Properties, Light Transmittance & Reflection	90.5%/8.2%/8.2%	90.0%/8.1%/8.1%	NPD	NPD	NPD	NPD	NPD
Radiation Properties, Solar Energy Characteristics	87%/7.8%/7.8%	84.9%/7.6%/7.6%	NPD	NPD	NPD	NPD	NPD

The performance of the product identified above is in the conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed:		
Position:	QUALITY, H&S MANAGER.	
Location:	SGP, HD3 4NY	Date: 06-01-25